

# Hyperchill BioEnergy

## Water Chillers for Biogas & Landfill Gas Cooling Applications



Bioenergy is renewable energy stored in organic materials such as plant matter and animal waste, known as biomass. The wide variety of biomass fuel sources include agricultural residue, pulp/paper mill residue, urban wood waste, forest residue, energy crops, landfills and animal waste. Anaerobic digestion is the process that occurs when bacteria decompose organic materials in the absence of oxygen to generate biogas.

Biogas is primarily composed of methane and carbon dioxide with smaller amounts of hydrogen sulphide and ammonia. Trace amounts of other gases like hydrogen, nitrogen or carbon monoxide are also present in the biogas. Usually the mixed gas is saturated with water-vapour and may contain dirt particles. For biogas as a fuel, most of the impurities have to be removed, as they can cause contamination, deposits and damage to equipment. In particular, biogas needs to be dried by cooling it to temperatures close to 5°C, using water-cooled heat exchangers fed by water chillers. Hyperchill Bioenergy is a key component in this biogas treatment process.

Extremely compact and easy to use, Hyperchill Bioenergy ensures an accurate control of the water temperature. It has been specifically designed for Biogas applications and provides safe and reliable operation in the harshest of environments, typically found in Anaerobic Digesters and landfill Biogas production areas.



### Features and Benefits

- Special protective treatment of condensers and copper piping to ensure reliable operation in the most aggressive of ambient atmospheres at biogas plants and landfill sites.
- Pump and tank installed inside the chiller provides a compact and easy to install solution.
- Closed water temperature operation with high working limits and low running costs.
- Large built-in water tank that provides a large thermal mass / storage capacity thus reducing the number of refrigerant compressor stop/starts and short cycling and thereby increasing the compressor and chiller lifetime.
- Designed to provide cooling water where low temperature water is required as standard (Air Conditioning units do not normally need to provide water at less than 10°C).
- Use of compliant scroll compressors designed specifically for high efficiency and long life in industrial applications.
- Low ambient speed-control on fan-motor ensures constant performances at different temperatures, long lifetime of the fans and a reduction in absorbed power when ambient temperature is low.
- Maximum working ambient temperature up to 48°C for ICEP models, up to 45°C for ICE models, prevents downtime even under extremely harsh conditions

# Hyperchill BioEnergy 007-360

The performance of biogas as a fuel depends on effective cooling and treatment. Saturated biogas contains water and impurities that need to be removed to avoid damage to equipment and to reach more efficient combustion, whilst maintaining the desired dew point.

- **Water and refrigerant manometers** permit full control of the working conditions.
- **Microprocessors:** allow complete control of the unit parameters. Proprietary software allows a wide range of programming and remote monitoring options.
- **Compliant scroll compressors:** with less moving parts and compliant-technology, they provide excellent efficiency, high reliability, and very low noise levels.
- **Air cooled with axial fans:** suitable for outdoor installation.
- **Water pump (std 1,5 bar):** available with different head pressures to suit the end-users application. Configurable as a twin-system, for 100% redundancy.
- **Mesh filters:** condenser protection against dirt and contamination, reduces maintenance costs and the risk of downtime.
- **Evaporator:** located inside the water tank from ICE076 - reduces the overall dimension of the unit, increases the efficiency and improves temperature control.
- **Water by-pass:** protects the pump and supplies constant flow to the evaporator, avoiding alarms and freezing.
- **Water tank:** stainless steel up to ICEP060 generously dimensioned to guarantee high reliability and improved temperature-control.
- Models from ICEP020 to ICEP060 designed with fan control in order to work as standard in low ambient temperatures down to -10°C.
- Maximum ambient temperature 48 °C up to ICEP060, 45°C from ICE076.
- MODBUS interface fitted on ICEP models; optional for ICE models

## Options

- **Special and multiple-pumps:** higher (P30-3bar) head pressure available to suit different hydraulic circuits. Double stand-by pump for greater reliability.
- **Antifreeze heating:** avoids freezing when the unit is switched off. Can also be used as a heater to warm up the system.
- **Water fill-kits:** pressurized, automatic or ambient manual kits, for water filling in any installation.
- **Remote control kits:** base version for remote ON/OFF and general alarm monitoring. Advanced version for complete remote unit management.
- **Wheels (up to ICEP014 BioEnergy):** for ease of transport.



# Product-Specification

## Hyperchill BioEnergy 007-360

Model		ICEP									ICE							
		007	010	014	020	024	030	040	050	060	076	090	116	150	183	230	310	360
Cooling Capacity <sup>1</sup>	kW	7.8	10.8	14.6	20.3	23.6	29.7	40.6	49.0	58.3	76.0	90.2	115.5	149.2	182.3	228	305.1	359.7
Compr. abs. power <sup>1</sup>	kW	1.7	2.5	3.2	4.4	5.4	5.7	7.5	10.0	12.3	15.4	20.3	24.9	30.8	40.1	51.4	64.2	81.5
SEPR HT <sup>5</sup>		5.00	5.22	5.30	5.02	5.02	5.00	5.13	5.12	5.11	5.39	5.04	5.08	5.35	5.04	5.02	5.51	5.73
Cooling Capacity <sup>2</sup>	kW	4.4	5.6	7.6	11.5	13.5	16.9	23	27.7	33.0	43.2	51.7	66.1	85.3	104.2	130.2	180.5	205.7
Compr. abs. power <sup>2</sup>	kW	1.4	1.9	2.7	3.5	4.3	6.4	8.2	10.7	13.1	16.4	20.8	26.4	32.5	41.4	55.1	63.4	83.2
Power supply	V/ph/Hz	400/3/50 no neutral																
Protection class		54																
Refrigerant		R407C																

### Compressors

Type		scroll									hermetic compliant scroll							
Compressor / circuits		1/1									2/2				4/2			
Max. abs. power-1 compr.	kW	2.4	3.8	4.4	5.7	6.6	8.3	11.4	14.9	17.3	11.1	13.7	16.8	11.1	13.7	16.8	23.3	28.7

### Axial fans

Quantity	N°	1			2						3			2		3		4	
Max. abs. power-1 fan	kW	0.3	0.3	0.4	0.4	0.4	0.45	0.69	0.69	0.69	0.78	0.78	0.78	2	2	2	2	2	2
Total air flow	m³/h	3437	3437	4337	6878	6159	9437	16029	15215	16875	25500	25000	26400	47000	46000	66000	88000	88000	

### PumpP15

Type		centrifugal																
Max. abs. power	kW	0.4	0.4	0.4	0.5	0.5	0.55	0.55	0.75	0.75	1.1	1.1	1.1	1.5	1.5	2.2	on request	
Water flow (nom/max) <sup>1)</sup>	m³/h	1.3/4.2	1.8/4.2	2.5/4.2	3.4/7.2	4.1/7.2	5.1/11	6.9/11	8.4/18	10.1/18	12/25	15/825	19/44	25/44	30/44	39/48		
Head pressure (nom/min) <sup>1)</sup>	mH <sub>2</sub> O	19/9	15/9	17/9	18/7	17/7	16/12.5	14/12.5	16/10	13/10	15/8	15/8	13/6	12/6	10/6	14/8		
Water flow (nom/max) <sup>2)</sup>	m³/h	0.9/4.2	1.2/4.2	1.6/4.2	2.4/7.2	2.8/7.2	3.7/11	5/11	6/11	7.1/18	9.0/25	11/25	13/44	18/44	22/44	28/48		
Head pressure (nom/min) <sup>2)</sup>	mH <sub>2</sub> O	20/9	19/9	17/9	20/7	19/7	20/12.5	16/12.5	20/10	17/10	16/8	16/8	13/6	11/6	12/6	20/8		

### Dimensions & Weight

Width	mm	756	756	756	756	756	756	856	856	856	898	898	898	1287	1287	1287	1500	1500
Depth	mm	806	806	806	1206	1206	1206	1956	1956	1956	2200	2200	2200	3000	3000	3260	4200	4200
Height	mm	1405	1405	1405	1405	1405	1405	1680	1680	1680	1984	1984	1984	2298	2298	2298	2240	2240
Connection in / out	in	3/4"	3/4"	3/4"	1"	1"	1"	1" 1/2	1" 1/2	1" 1/2	2"	2"	2"	2 1/2"	2 1/2"	2 1/2"	4"	4"
Tank Capacity	l	65	65	65	100	100	130	250	250	250	500	500	500	1000	1000	1000	400	400
Weight (axial) <sup>3)</sup>	kg	160	165	175	220	220	250	450	470	510	800	900	1000	1500	1800	2100	2900	2900

### Noiselevel

Noise level <sup>4)</sup>	dB(A)	53	53	50	50	50	51	52	52	53	58	58	58	62	62	64	65	65
---------------------------	-------	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----	----

<sup>1)</sup> data refers to water inlet/outlet temperature = 20/15°C, glycol 0 %, ambient temperature 25°C.

<sup>2)</sup> data refers to water inlet/outlet temperature = 5/1°C, glycol 10 %, ambient temperature 35°C.

<sup>3)</sup> weights are inclusive of pallet and refrigerant charge.

<sup>4)</sup> in free field conditions at a distance of 10 m from the unit, measured on condenser side, 1m from ground.

All models supplied with R407C and with power supply 400V / 3ph / 50Hz.

<sup>5)</sup> Value calculated in accordance with the European regulation (EU) 2016/2281 with regards to Ecodesign requirements for high temperature process chillers;

As the manufacturer of process chillers delivering water at a design temperature of 15 °C, Parker Hannifin Manufacturing s.r.l., Gas Separation and Filtration Division EMEA, declares that Parker chillers are exempt from Ecodesign EU regulation 2016/2281.

### Correctionfactors

A) Ambient temp. (air-cooled models) correction factor (f1)	°C	5	10	15	20	25	30	35	40	45
		1,05	1,05	1,05	1,05	1	0,95	0,89	0,83	0,77
B) Water outlet temperature correction factor (f2)	°C	5	10	15	20	25				
		0,72	0,86	1	1	1				
C) Glycol correction factor (f3)	%	0	10	20	30	40	50			
		1	0,99	0,98	0,97	0,96	0,94			

To obtain the required cooling capacity multiply the value at nominal conditions by the above correction factors (i.e. cooling capacity = Pxf1xf2xf3, where P is the cooling capacity at conditions (1)). The above correction factors are approximative: for a precise selection always refer to the software selection program.

# Parker Worldwide

## Europe, Middle East, Africa

### AE – United Arab Emirates,

Dubai

Tel: +971 4 8127100

### AT – Austria, St. Florian

Tel: +43 (0)7224 66201

### AZ – Azerbaijan, Baku

Tel: +994 50 2233 458

### BE/NL/LU – Benelux,

Hendrik Ido Ambacht

Tel: +31 (0)541 585 000

### BY – Belarus, Minsk

Tel: +48 (0)22 573 24 00

### CH – Switzerland, Etoy

Tel: +41 (0)21 821 87 00

### CZ – Czech Republic,

Prague

Tel: +420 284 083 111

### DE – Germany, Kaarst

Tel: +49 (0)2131 4016 0

### DK – Denmark, Ballerup

Tel: +45 43 56 04 00

### ES – Spain, Madrid

Tel: +34 902 330 001

### FI – Finland, Vantaa

Tel: +358 (0)20 753 2500

### FR – France, Contamine s/Arve

Tel: +33 (0)4 50 25 80 25

### GR – Greece

Tel: +30 69 44 52 78 25

### HU – Hungary, Budaörs

Tel: +36 23 885 470

### IE – Ireland, Dublin

Tel: +353 (0)1 466 6370

### IL – Israel

Tel: +39 02 45 19 21

### IT – Italy, Corsico (MI)

Tel: +39 02 45 19 21

### KZ – Kazakhstan, Almaty

Tel: +7 7273 561 000

### NO – Norway, Asker

Tel: +47 66 75 34 00

### PL – Poland, Warsaw

Tel: +48 (0)22 573 24 00

### PT – Portugal

Tel: +351 22 999 7360

### RO – Romania, Bucharest

Tel: +40 21 252 1382

### RU – Russia, Moscow

Tel: +7 495 645-2156

### SE – Sweden, Borås

Tel: +46 (0)8 59 79 50 00

### SL – Slovenia, Novo Mesto

Tel: +386 7 337 6650

### TR – Turkey, Istanbul

Tel: +90 216 4997081

### UK – United Kingdom, Warwick

Tel: +44 (0)1926 317 878

### ZA – South Africa, Kempton Park

Tel: +27 (0)11 961 0700

## North America

### CA – Canada, Milton, Ontario

Tel: +1 905 693 3000

### US – USA, Cleveland

Tel: +1 216 896 3000

## Asia Pacific

### AU – Australia, Castle Hill

Tel: +61 (0)2-9634 7777

### CN – China, Shanghai

Tel: +86 21 2899 5000

### HK – Hong Kong

Tel: +852 2428 8008

### IN – India, Mumbai

Tel: +91 22 6513 7081-85

### JP – Japan, Tokyo

Tel: +81 (0)3 6408 3901

### KR – South Korea, Seoul

Tel: +82 2 559 0400

### MY – Malaysia, Shah Alam

Tel: +60 3 7849 0800

### NZ – New Zealand, Mt Wellington

Tel: +64 9 574 1744

### SG – Singapore

Tel: +65 6887 6300

### TH – Thailand, Bangkok

Tel: +662 186 7000

### TW – Taiwan, Taipei

Tel: +886 2 2298 8987

## South America

### AR – Argentina, Buenos Aires

Tel: +54 3327 44 4129

### BR – Brazil, Sao Jose dos Campos

Tel: +55 080 0727 5374

### CL – Chile, Santiago

Tel: +56 22 303 9640

### MX – Mexico, Toluca

Tel: +52 72 2275 4200